

SUBAREA C5

Subarea C5 is located south of Davidson Road, west of I-270, and west of the Britton Parkway Extension. The site is 18.7 +/- acres.

I. Permitted Uses

1. The uses listed below shall be permitted uses within this Subarea.
 - a) Institutions and Offices
 - b) Public Uses
 - c) Semipublic Uses
 - d) Regional and Professional Offices
 - e) Professional Activities
2. Hotels shall be permitted, subject to conditional use review by the Planning Commission.
3. Restaurants shall be permitted within office buildings, as long as they are oriented toward the central green along Proposed Roads "D" and "F", subject to conditional use review by the Planning Commission.
4. Banks shall be permitted within office buildings, subject to conditional use review by the Planning Commission.
5. Parking Garages shall be permitted, subject to conditional use review by the Planning Commission.

II. Unit Types

Office buildings shall comply with the design guidelines of the development standards in this text.

III. Development Standards

Unless otherwise specified in the submitted drawings or in this written text the development standards of Chapter 1157 of the Codified Ordinances of the City of Hilliard shall apply to this subarea. Basic development standards are compiled regarding proposed density, site issues, traffic, circulation, landscape and architectural standards. These component standards ensure consistency and quality throughout the parcel's development.

C5.01 Density, Height, Lot and/or Setback Commitments

1. There shall be a maximum of 16,000 square feet per acre.
2. There shall be a minimum building footprint of 20,000 square feet.
3. There shall be a minimum size of 40,000 square feet per building and a minimum height of 2 stories.
4. The lot coverage shall not exceed 40% as defined by Hilliard City Code Section 1127.03. Total impermeable surface coverage shall not exceed 70%.

5. The maximum height limit shall be 45 feet.
6. The minimum building height for all buildings facing Britton Parkway Extension shall be 3 stories. All other buildings shall be a minimum of 2 stories.
7. There shall be a minimum side yard of 20 feet.
8. There shall be a minimum rear yard of 30 feet.
9. There shall be a 15 foot building and 20 foot pavement setback from the right-of-way of Proposed Road "D". This 15 foot building setback shall be a build-to line.
10. There shall be a 30 foot building and 50 foot pavement setback from the right-of-ways of Anson Drive and Proposed Road "F".
11. There shall be a 50 foot building and pavement setback from the Britton Parkway Extension right-of-way.

C5.02 Access, Loading, Parking and/or Traffic Related Commitments

1. Parking and loading requirements for an individual use within Subarea C5 shall be as set forth in Hilliard City Code Chapter 1133.
2. Cross-access easements shall be provided within this subarea where feasible.
 3. Vehicular access points permitting all movements shall be located no closer than 800 feet (centerline to centerline). Access points with left turn outbound movements restricted (i.e. not permitted) will be located no closer than 400 feet (centerline to centerline). Right turn movements in and/or out will be located not less than 200 feet apart, and considered on a location by location basis. All access points shall be subject to the review and approval of the Hilliard City Engineer.
 4. Along Britton Parkway between Davidson Road and Ansmil Boulevard, no left-turns out will be allowed at any driveway or side street. The developer has the right to have one full access point midway between Ansmil Boulevard and Anson Drive accessing Subareas C3 and C5. This intersection may be signalized in the future if warranted. At all other drives between Ansmil Boulevard and Anson Drive, no left-turns out will be allowed.
 5. There shall be a 3' (ht.) hedge or earth mound along the pavement setback of Britton Parkway Extension, Proposed Roads "D", "E", "F" and Anson Drive wherever structures do not exist at the building setback line.

C5.03 Architectural Standards

Buildings shall be oriented toward the central green with parking behind. Building materials shall be compatible with other uses surrounding the central green.

The building materials and design shall be consistent and compatible with buildings along the I-270 outerbelt between Cemetery Road and Sawmill Road.

1. Color Palette: Buildings shall be constructed of subdued, earth tone materials; muted colors are preferred. Accent colors brighter hues are permitted for building accent features only.

2. Materials: Brick, stone, stucco stone, pre-cast concrete, metal and glass are all permitted building materials.
3. Roof: Flat roofs are permitted, provided all roof top mechanical units are fully screened from view.
4. Articulation and Fenestration: Buildings shall have a consistent finish on all four sides. Fenestration shall be proportional with building size and massing.
5. Lot Coverage: Lot coverage shall not exceed 70% impervious surface. Impervious surface shall be defined as the building footprint and all paved surfaces including parking lots, but shall include any interior parking lot landscaping or other similar unpaved surfaces.
6. Side Yard Standards: A minimum building side yard of 1/4 the sum of the height of the structure and the length of the wall parallel to the side lot line (1/4 (height + length)). In no case shall the side yard be required to be more than 50 feet or less than 20 feet.

C5.04 Buffering, Landscaping, Open Space and/or Screening Commitments

1. Landscaping
 - a) All landscaping shall be in accordance with the requirements of Hilliard City Code Section 1331.
 - b) Any portion of a lot upon which a building or parking area is not constructed shall be landscaped with lawn as a minimum. Those areas designated as landscaped buffers, tree lawns, tree preservation zones, entry features or other landscaped features shall be maintained meeting the minimum standards in Hilliard Codified Ordinances Chapters 917, 921 and 1331. The use of in-ground sprinkler systems, where appropriate, is strongly encouraged.
 - c) Interior landscaping for vehicular use areas: Any open vehicular use area, excluding loading, unloading and storage areas in an industrial zone or business zone, containing more than 6,000 square feet of area, or twenty or more vehicular parking spaces, shall provide interior landscaping in addition to previously required perimeter landscaping. Interior landscaping may be peninsular or island types.
 - d) Landscape Area: For each 100 square feet or fraction thereof, of vehicular use area, a minimum total of five square feet of landscaped area shall be provided.
 1. Minimum area: The minimum landscape area permitted shall be sixty-four square feet with a four-foot minimum dimension to all trees from edge of pavement where vehicles overhang.
 2. Maximum contiguous area: In order to encourage the required landscape areas to be properly dispersed, no individual landscape area shall be larger than 350 square feet in size, and no individual area shall be larger than 1,500 square feet in vehicular use areas over 30,000 square feet. In both cases, the least dimension of any required area shall be four feet minimum dimension to all trees from edge of pavement where vehicles overhang. Individual landscape

areas larger than above are permitted as long as the additional area is in excess of the required minimum total.

- e) Minimum trees: The following minimums are required, based upon total ground coverage of structures and vehicular use areas:
1. Up to 20,000 square feet: A minimum of one tree per 5,000 square feet of ground coverage, and a total tree planting equal to 1 inch in tree trunk size for every 2,000 square feet of ground coverage.
 2. Between 20,000 and 50,000 square feet: A minimum of one tree for every 5,000 square feet of ground coverage, and a total tree planting equal to ten inches plus one-half inch in tree trunk size for every 2,000 square feet over 20,000 square feet in ground coverage.
 3. Over 50,000 square feet: A minimum of one tree for every 5,000 square feet of ground coverage, and a total tree planting equal to twenty-five inches plus one-half inch in tree trunk size for every 4,000 square feet over 50,000 square feet of ground coverage.
 4. Trees shall have a clear trunk of at least five feet above the ground, and the remaining area shall be landscaped with shrubs, ground cover, not to exceed two feet in height.
- f) Protection of Landscaped Islands: Parked vehicles may hang over the interior landscaped area not more than two and one-half feet, as long as concrete or other well stops are provided to insure no greater overhang or penetration of the landscaped area. All parking spaces and landscaped islands shall meet the requirements of the Hilliard Codified Ordinances, Chapters 1133 and 1331.
- g) Curbs to protect screening material: Whenever screening material is placed around any trash disposal unit or waste collection unit which is emptied or removed mechanically on a regularly occurring basis, a curb to contain the placement of the container shall be provided within the screening materials on those sides where there is such material. The curbing shall be at least one foot from the material and shall be designed to prevent possible damage to the screening when the container is moved or emptied.
- h) Tree Planting Requirements: There shall be tree plantings equal to one-half inch in tree trunk size for every 150 square feet in ground coverage by a residential structure. These trees shall be a minimum of 2" caliper at the time of installation.
1. No new tree planting shall be required if existing trees and the aggregate trunk sizes of such trees meet or exceed the requirements as set forth in this chapter. The minimum tree size for such tree plantings shall be no less than one and one-half inch in trunk diameter.
 2. The applicant or owner shall plant such trees as may be required within one year or the next planting season after issuance of a building permit. Failure to comply with the landscaping requirements shall be in violation of this section and be subject to citation.

- i) Landscape Materials:
 - 1. Plants: Artificial plants are prohibited. All plant materials shall be living plants and shall meet the following requirements:
 - a. Quality: Plant materials used in conformance with the provision of this chapter shall conform to the standards of the American Association of Nurserymen and shall have passed any inspections required under State regulations.
- j) Within the 50 foot setback from the right-of-way of Britton Parkway Extension, there shall be a 4' (ht.) continuous meandering and undulating earth mound, except for areas of ingress and egress for roadways and ponds. The mound will have a \pm 6:1 slope that will begin at the right-of-way line. The mound will also have a 3:1 slope on the opposite side which will begin at the 50 foot setback line so that the crest of the earth mound will begin approximately 12-15 feet from the setback line and extend for approximately 5 feet in width. Along the crest of the earth mound will be a continuous 3' (ht.) evergreen hedge.
- k) Street trees shall be planted at a minimum distance of 40 feet on center along Anson Drive and Proposed Roads "D" and "F". There will be a double row of street trees planted along Britton Parkway Extension at a distance of 40 feet on center and spaced 25 feet between. Trees will be of a deciduous species normally attaining full grown height in excess of 50 feet and will be of 2 ½" caliper or greater at the time of planting.
- l) There shall be a 3' (ht.) hedge or earth mound along the pavement setback of Britton Parkway Extension, Anson Drive, and Proposed Roads "D", "E", and "F" wherever structures do not exist at the building setback line.
- m) Fencing shall be permitted within this subarea with conditional use approval.
- n) Landscape plans shall be reviewed and approved by the Hilliard Shade Tree Commission at the Final Development Plan stage.

C5.05 Dumpsters, Lighting, Outdoor Display Areas and/or other Environmental Commitments

1. All parking lot lighting shall not exceed 18 feet in height from finished grade.
2. External lighting shall be cut-off type fixtures.
3. There shall be a consistent and uniform lighting fixture for parking lot lighting within all office areas, as approved by the Hilliard City Engineer.
4. All types of parking, pedestrian and other lighting shall be on poles or wall mounted cut-off fixtures and shall be from the same type and style.
5. All light poles and standards shall be metal and shall be black or dark bronze in color.
6. Parking lot lighting shall be high pressure sodium. Building and landscaping lighting shall be

incandescent or metal halide.

7. Landscape and building uplighting from a concealed source shall be permitted.
 8. All lights shall be arranged to reflect light away from any street or adjacent property.
 9. All building illumination shall be from concealed sources.
 10. No colored lights shall be used to light the exterior of the buildings.
11. Waste and Refuse:
- a) All waste and refuse shall be containerized and screened from view on-three sides by a solid brick wall, wood fence, or materials compatible with building materials and at least 6 inches taller than the height of the dumpster. The fourth side shall contain a wood gate at least 6 inches taller than the height of the dumpster.
12. Storage and Equipment and Service Areas:
- a) No materials, supplies, equipment or products shall be stored or permitted to remain on any portion of the parcel outside the permitted structure. Mechanical equipment or other utility hardware on roof, ground, or buildings shall be screened from view with material harmonious with the building.
 - b) All refuse trash and garbage collection shall be enclosed or not visible from the street or adjoining property.
 - c) No noises, smoke, odors, vibration or other nuisances shall be permitted.
 - d) No area of the site will be used for outdoor storage.
 - e) Service courts and loading docks shall be screened from all streets or adjacent buildings by landscaping, mounding or walls.

C5.06 Graphics and Signage Commitments

1. All signage and graphics shall conform to the Hilliard Graphics and Sign Code Chapter 1191.
2. The development shall utilize standard City of Hilliard street and regulatory signage. Other signage may be used subject to approval by the City of Hilliard Graphics Commission.

C5.07 Miscellaneous Commitments

1. Utilities: All utility lines including water service, electricity, telephone and gas, and their connections or feeder lines shall be placed underground. Provided, however, that the existing overhead transmission lines shall remain above ground. Meters, transformers, etc. may be placed above ground, but shall be screened from view. Where feasible, all above ground utility boxes shall be placed at the rear lot lines or sufficiently screened.